



ATC8050

Speaker Cable

PACKAGE 100m/roll

NUMBER OF CORES 2

CONDUCTORS

Material Oxygen Free Copper

AWG 15

Strand Diameter 0.2 mm

Strand Quantity 48 pcs

Core Area 1.5 sq.mm

Stranding 48 x 0.2 mm

INSULATION

Material PVC

Thickness 0.5 mm

OUTER JACKET

Material PVC

Thickness 1.1 mm

OVERALL STRUCTURE

Overall Nom. Diameter 7 mm

Overall Nom. Weight 76 g/m

ELECTRICAL CHARACTERISTICS

Nom. Characteristic Impedance 14 Ohm/km

Nom. Capacitance Conductor to Conductor 189 pf/m

Nom. Conductor DC Resistance 14 Ohm/km

Max. Operating Voltage 500 V

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

EU RoHS Compliant Yes

EU RoHS Compliance Date Nov-05

ENGINEERED BY AUSTRALIAN MONITOR

Address: 1 Clyde Street, Silverwater, Sydney NSW 2128 Australia. Private Bag 149, Silverwater NSW 1811 ABN 35 007 573 417

Website: www.australianmonitor.com.au International enquiries email: international@australianmonitor.com.au

DISTRIBUTED IN AUSTRALIA AND NEW ZEALAND BY HILLS SVL www.hillssvl.com.au

NSW P: 02 9647 1411 QLD P: 07 3852 1312 ACT P: 02 6260 4544 WA P: 08 9204 0200 VIC P: 03 9890 7477 SA P: 08 8408 8300 NZ P: 09 415 9426

E: nsw@hillssvl.com.au E: qld@hillssvl.com.au E: act@hillssvl.com.au E: wa@hillssvl.com.au E: vic@hillssvl.com.au E: sa@hillssvl.com.au E: sales@hillssvl.co.nz