



**TX30  
30 watt  
4 CHANNEL  
MIXER  
AMPLIFIER**

Compact 30 watt RMS amplifier with two mic/line balanced inputs and two auxiliary inputs.

TX 30 is only one rack height and **FEATURES** include:—

- Low profile table or rack mounting
- Tape recorder output
- 100 & 70 volt plus 8 ohms output
- XLR mic sockets, RCA line sockets
- LED level indicator
- Provision for plug in mic precedence (muting)
- Phantom power voltage at mic sockets (for electret)
- 240 VAC or 24 VDC power source

**Technical Specifications:**

MIC INPUT SENSITIVITY	.65 MV 200 ohms transformer balanced
LINE INPUT SENSITIVITY	50 MV and 22 K ohms
AUX INPUT SENSITIVITY	100 MV 10 K ohms
FREQUENCY RESPONSE	50 Hz to 17 KHz ± 3 dB
SIGNAL TO NOISE	−72 dBm with respect to 100 V out
OUTPUTS AVAILABLE	100 + 70 volts, 600 ohms, 8 ohms, rec out
DISTORTION	0.06% THD
PHANTOM POWER	1.5 VDC at XLR mic socket
OPERATING VOLTAGE	240 VAC, 24 VDC
DIMENSIONS	482 W × 250 D × 44 H mm
WEIGHT	5 Kg