



The TX4010 is a compact single rack height, desk or rack mounting unit, which combines microphone/auxiliary mixer, monitor amplifier speaker, bell tone generator and emergency evacuation signal. Both the bell and evacuate tones can be actuated from the front panel or remotely turned on/off if desired.

TX4010 will accept up to four balanced mic inputs and three auxiliary inputs (switched). It will provide sufficient output levels to drive most power amplifiers.

The unit is ideally suited for most PA systems, which utilize a programme source such as a tape recorder, compact disc, radio or land line. It will enable pre-monitoring by turning the master volume control to zero and utilising the separate volume control for speaker monitoring.

Inbuilt tone generators are a feature of the TX4010, the bell tone is a simulated electric bell, the evacuation tone complies with AS2220.1. Both generators can be operated from a separate time switch or other normally open contact.

TECHNICAL SPECIFICATIONS:

MIC INPUT SENSITIVITY	0.6MV XLR Sockets
AUX INPUT SENSITIVITY	200MV RCA Sockets
LINE INPUT SENSITIVITY	50MV
FREQUENCY RESPONSE	50Hz - 16KHz
SIGNAL TO NOISE	-77dB
OUTPUT	Transformer Balanced 3 volts RMS
DISTORTION THD	0.5%
MONITOR SPEAKER AMPLIFIER	Two Watts
BELL TONE GENERATOR	Simulated Electric Bell
EVACUATION TONE GENERATOR	To AS2220.1 (MANUAL)
OPERATING VOLTAGE	240/120 VAC 24 VDC
DIMENSIONS	482 W x 250 D x 44 H mm
OTHER FEATURES	<ul style="list-style-type: none"> — Phantom power at mic inputs — Priority muting mic 1, mutes all other inputs — Tape record output — Optional plug in mic/line transformer

FEATURES:

- **Four Balanced Mic Inputs**
- **Three Aux Inputs Selectable**
- **Inbuilt Speaker Monitor**
- **Bell & Evacuation Tones**