



Australian Monitor

KA1500



LOW COST, NO COMPROMISE 750+750 WATTS

The Australian Monitor KA1500 provides serious performance for not so serious dollars.

A professional amplifier in this price range with this sort of superior sonic performance and the flexibility of accepting optional plug-in active filters and limiters, was unheard of before the Australian Monitor KA range.

Having built our reputation in the demanding concert and large installation markets, we now offer a high value for money amplifier that all venues can enjoy.

FEATURES:

- 2RU Heavy Duty custom alloy chassis
- Modular Construction - easy service
- Symmetrical Layout - even weight distribution
- Binding posts and 'speakon' outputs
- Balanced inputs and buffered attenuators
- Optional Plug in signal modifiers, high pass & low pass filters plus limiter module
- Quad twin speed axial fans
- Efficient front to back cooling
- 21 position detented attenuators
- 1 watt and clipping indicators



SITUATION CRITICAL
RELIABILITY IS EVERYTHING

KA1500**Output Power RMS (per channel)**

8 ohm	4 ohm	2 ohm
500 watts	750 watts	1000 watts

Output Power RMS (bridge mode)

16 ohm	8 ohm	4 ohm
1000 watts	1500 watts	2000 watts

PROTECTION:

- Independent rail fuses
- Input muting at turn on
- Input over voltage protection
- R.F. Interference suppression
- Short circuit protection and indication
- Thermal overload protection
- Mains inrush current suppression and indication
- Layout, grounding, decoupling and componentry have been optimised to provide the user with stability, reliability and longevity.

OPTIONS:

- High Pass Filter card HP1
- Low Pass Filter card LP1
- Limiter card LIM1
- Clip Limiter Card CLIM1

**SPECIFICATIONS:**

Output Impedance @ 1 kHz:	<0.025 ohms
Damping Factor @ 1 kHz re 8 ohms:	>350:1
Output Rise Time:	<3.5 μ S (80%, leading edge of 20kHz square wave)
Slew Rate:	60V per μ S (leading edge, 20kHz square wave @ clipping)
Weight:	Net 41.8 lb (19kg), Shipping 47.3 lb (21.5kg)
Distortion (0.5 dB below clipping re 4 ohms):	THD+N (@ 1 kHz) <0.01%
Frequency Response:	20 Hz - 20 kHz \pm 0.15 dB -3dB points <10 Hz - 80 kHz
Input Impedance:	Line to Line (Balanced) 30k ohms
Input Sensitivity (nominally):	For rated power re 8 ohm 1.26 Vrms (+4 dBu) For rated power re 4 ohm 1.10 Vrms (+3 dBu)
Signal/Noise ratio:	"A" weighted (re 8 ohm rating) >105 dB
Crosstalk:	@ 1 kHz (re 8 ohm rating) >90 dB
Dimensions:	excluding handles 3.5h x 19w x 14.8d (inch) 88h x 482h x 375w (mm) including handles 3.5h x 19w x 18.3d (inch) 88h x 482w x 465d (mm) (19 inch EIA rack mounting, 2 units high) 240 & 110V versions available
Power:	

**OTHER MODELS IN THE KA SERIES FAMILY ARE AVAILABLE.
CONTACT YOUR LOCAL DEALER OR NEAREST AUDIO TELEX OFFICE.**



**AUSTRALIAN, NEW ZEALAND
EXPORT WEBSITE:**
www.audiotellex.com.au

NSW: Tel: (02) 9647 1411 Fax: (02) 9648 3698
VIC: Tel: (03) 9890 7477 Fax: (03) 9890 7977
QLD: Tel: (07) 3852 1312 Fax: (07) 3252 1237
WA: Tel: (08) 9228 4222 Fax: (08) 9228 4233
TAS: Tel: (03) 6228 6373 Fax: (03) 6278 1063
SA: Tel: (08) 8352 4444 Fax: (08) 8352 4488
NZ: Tel: (09) 415 9426 Fax: (09) 415 9864

Authorised dealer:

