

# WCM5

## 5" Wall Mount Speaker

### Features

- High quality voice/music reproduction
- Clean aesthetic appearance
- 100V constant voltage
- Integrated volume control
- Volume bypass relay
- Supervisory capacitor
- CE Approved



### Specifications

Description	5" Wall Mount Speaker with volume control, bypass relay & supervisory blocking capacitor
Enclosure	Plastic, RAL9016 white
Grill	Perforated Mild Steel
Driver	5" paper twin cone with 20mm voice coil
Nominal Driver Impedance	8 Ohms
Transformer Impedances	2K, 4K, 10K, 20K, 30K Ohms
Power Taps (100V)	5W, 2.5W, 1W, 0.5W, 0.33W
Power Taps (70V)	2.5W, 1W, 0.5W, 0.25W, 0.165W
Frequency Response ( $\pm 1$ dB)	140 Hz - 20 kHz
Sensitivity (1W/1M) half space	88 dB
Maximum SPL (1M, Continuous)	95 dB
Continuous Power Handling (IEA RS 426)	5 W
Bypass Relay	24 VDC
Dimensions (H x W x D) mm	170 x 234 x 75 mm
Net Weight	1.05 kg

#### ENGINEERED BY AUSTRALIAN MONITOR

Address: 1 Clyde Street, Silverwater, Sydney NSW 2128 Australia. Private Bag 149, Silverwater NSW 1811 ABN 35 007 573 417

Website: [www.australianmonitor.com.au](http://www.australianmonitor.com.au) International enquiries email: [international@australianmonitor.com.au](mailto:international@australianmonitor.com.au)

#### DISTRIBUTED IN AUSTRALIA AND NEW ZEALAND BY HILLS SVL [www.hillssvl.com.au](http://www.hillssvl.com.au)

NSW P: 02 9647 1411 QLD P: 07 3852 1312 ACT P: 02 6260 4544 WA P: 08 9204 0200 VIC P: 03 9890 7477 SA P: 08 8408 8300 NZ P: 09 415 9426  
E: [nsw@hillssvl.com.au](mailto:nsw@hillssvl.com.au) E: [qld@hillssvl.com.au](mailto:qld@hillssvl.com.au) E: [act@hillssvl.com.au](mailto:act@hillssvl.com.au) E: [wa@hillssvl.com.au](mailto:wa@hillssvl.com.au) E: [vic@hillssvl.com.au](mailto:vic@hillssvl.com.au) E: [sa@hillssvl.com.au](mailto:sa@hillssvl.com.au) E: [sales@hillssvl.co.nz](mailto:sales@hillssvl.co.nz)